Rubino 200 TTT

Rubino 200 TTT is a completely automatic table-top vending machine of the last generation with design and technical performance at the top of the range. It is equipped with the new Saeco TTT TwinTasteTech brewing unit that allows the dispensing of both paperless fresh brew coffee and espresso coffee without any software or mechanical presetting. The product can be selected by simply pressing a button on the direct access keypad.

Designed for small and medium locations, it is available with cabinet in two versions, standard and for payment system, and dispenses up to 8 different beverages.



Main features

- Automatically dispenses cups (up to 195), sugar and stirrers
- Paperless fresh brew and/or espresso coffee dispensing from ground coffee or coffee beans thanks to Saeco TTT TwinTasteTech brewing unit
- Accepts the most commonly used parallel and serial MDB, BDV and Executive (possible Master and Slave configurations) payment systems
- 6 gr to 10 gr adjustable doser
- Possibility to dispense products up to 10 ounces
- Standard CPU for the whole range
- Customisable settings
- High safety for customer and operator

Accessories

- Cabinet with height-adjustable feet (w x h x d 410 x 800 x 537 mm, 24 kg)
- Cabinet with height-adjustable feet suitable for changegiver (w x h x d 410 x 800 x 537 mm, 24 kg)
- Independent water tank kit
- Timekeeper kit
- 12 V DC validator kit
- Electromechanical pulse counter kit
- 5-button keypad kit
- Memory key to copy and quickly transfer machine settings
- Eva-Dts 6.0 kit



Ideas with Passion



Technical Data	Rubino 200 TTT
Dimensions (w x h x d)	410 x 757 x 537 mm
Weight	46 kg
Power supply	230 V/50 Hz 120 V/60 Hz
Power consumption	1250 W
Boiler	brass
Water connection	3/4" (1-8 bar)
Water supply	standard: water supply optional: independent water tank kit
Coffee bean container	1
Ground coffee containar	1
Instant product container	2
Sugar container	1
Disc mixer	2
Brewing unit	10 gr
Available cups ø	70 or 73 mm
Available stirrers	90 – 105 – 115 mm
Number of selections	8
Number of preselections	up to 4

Capacities	Rubino 200 TTT
Coffee beans	2.0 kg
Ground coffee	1.0 kg
Instant coffee	0.7 kg
Milk	0.85 kg
Chocolate	1.7 kg
Sugar	2.0 kg
Cups (h 70 mm)	195
Stirrers	180
Independent water tank	201

Always at your service:

Technical specifications

- Pre-galvanized and painted steel-sheet body
- Thermoplastic door
- Thermoplastic cover with transparent coffee bean container
- Containers and tanks in food-contact approved polypropylene
- Water, coffee and cup-empty signal
- · Software function setting the maximum number of coffee cycles permitted before the dump box is removed and emptied
- Electronically controlled boiler temperature
- Exhauster to absorb internal moisture and additional steam exhauster for the dispensing area
- Removable cup-releasing device for easy cleaning and checking
- 60 W electromagnetic vibration pump
- Anti-overflow air-break device
- Simplified error reset
- · Boiler safety valve
- · General safety relay for 24 V components
- · Thermal cut-outs on all devices supplied with line voltage
- CE, VDE and UL approved

User interface

- Direct access 8-button keypad for beverage selection
- 2 keys for sugar preselection
- · Option to set 2 preselection keys: one for decaffeinated/ barley and one for no-cup option
- 2-line, 20-character alphanumeric display
- Both fresh brew and espresso coffee can be selected using the direct access keypad





Mixed Sources Product group from well-managed forests and other controlled sources FSC www.fsc.org Zert. Nr. GFA-COC-001492 © 1996 Forest Stewardship Council

Saeco Vending S.p.A.

Località Casona, 1066 40041 Gaggio Montano, Bologna - Italy Tel: +39 0534 7741 - Fax: +39 0534 774808

info.saecovending@saeco.com www.saeco.com

As our Company is constantly involved in the continuous improvement of its production, aesthetic characteristics and dimensions, technical data, equipment and accessories can be subject to variation. For this reason the manufacturer reserves the right to make any changes without prior notice.